

NOTES:

INTERFACE CONFORMS TO CECC 22220 INTERFACE SPECFICATIONS FOR MCX SERIES

ELECTRICAL:

NOMINAL IMPEDANCE: 50Ω FREQUENCY RANGE: DC TO 6 GHz

MATERIALS:

INSULATOR: TEFLON PER ASTM-D-1710


CONTACT: BERYLLIUM COPPER PER ASTM-B-196


BODY, JAM-NUT, & WASHER: 360 ALLOY BRASS 1/2 HARD PER ASTM-B-16

FINISHES:

CONTACT: GOLD PLATE PER MIL-DTL-45204

BODY, JAM-NUT, & WASHER: GOLD PLATE PER MIL-DTL-45204





RECOMMENDED CABLE STRIPPING DIMS

t	DED BE ANY	APPD.	T.D.		LINII	ESS (
		DATE	4/6/17	-	DIMENSIC	
	EMBE THE L NC ONE OF A	BY	J.N.		TOLERAN	
		DATE	4/6/17			
	TARY NOT SIGNES AND ID SIGNES AND ID HIT RELATES SI THE DEVICE DISCLOSED TO WRITTEN CON PANY OFFICIAL	DESCRIPTION			MATERIAL:	SEE
	PROPRIET VING AND DESI VICE TO WHICH F PRODUCING COPIED OR D VITHOUT THE W	DESC	RELEASE		FINISH:	SEE
	. > < 0 :: > =		INITIAL R		DRAWN J.N.	
	THIS DRA IN THE DE METHOD (EMPLOYE MANNER (REV.	_		APPROVED A.T.	1

UNLESS OTHERWISE SPECIFIED:							
DIMENSIONS ARE IN INCHES: TOLERANCES: NONE						SCALE 4:1	
					0		8
MATERIAL: SEE	NOTES						TITL
FINISH: SEE	NOTES						
J.N.	DATE 4/6/17	T.D.)			ATE 17	
APPROVED A.T.	DATE 4/6/17	SHEET	1	OF	1		1



EZ Form Cable Corporation285 Welton Street
Hamden, CT 06517
WWW.ezform.com

MCX BULKHEAD JACK FOR .086" S/R CABLE

	CODE IDENT.
Α	9W826

701960-086MCX